

GTM ELECTRONICS

TO-220 Schottky Diodes

Part No.	Maximum Peak Reverse Voltage	IO @T _A = 25°C	IFSM	Maximum Reverse Current @T _A = 25°C		Maximum Forward Voltage @T _A = 25°C	
				I _R	V _R	I _{FM}	V _{FM}
				mA	V	A	V
GESBL1030CT	30	10	125	0.5	30	5	0.55
GESBL1035CT	35	10	125	0.5	35	5	0.55
GESBL1040CT	40	10	125	0.5	40	5	0.55
GESBL1045CT	45	10	125	0.5	45	5	0.55
GESBL1050CT	50	10	125	0.5	50	5	0.70
GESBL1060CT	60	10	125	0.5	60	5	0.70
GESBL1630CT	30	16	250	0.5	30	8	0.55
GESBL1635CT	35	16	250	0.5	35	8	0.55
GESBL1640CT	40	16	250	0.5	40	8	0.55
GESBL1645CT	45	16	250	0.5	45	8	0.55
GESBL1650CT	50	16	250	0.5	50	8	0.70
GESBL1660CT	60	16	250	0.5	60	8	0.70
GEMBR2070CT	70	20	150	0.1	70	20	0.95
GEMBR2080CT	80	20	150	0.1	80	20	0.95
GEMBR2090CT	90	20	150	0.1	90	20	0.95
GEMBR20100CT	100	20	150	0.1	100	20	0.95

量産	未量産	有様品	工程實驗未產出
----	-----	-----	---------