

GTM ELECTRONICS

SOT-23 Schottky Diodes

Part No.	Maximum Peak Reverse Voltage	IO @TA = 25°C	IFSM	Maximum Reverse Current @TA = 25°C		Maximum Forward Voltage @TA = 25°C		Cj	Marking Code
				IR	VR	IFM	VFM		
	V	mA	A	uA	V	mA	V	pF	
G400SD	40	500	3	50	30	500	0.55	20	05F
G401SD	30	200	3	100	30	200	0.5	40	05H
G402SD	30	300	3	100	30	300	0.5	40	05K
G411SD	40	500	3	30	10	10	0.3	20	05T
G420SD	40	100	1	1	10	10	0.45	6	LV5
G421SD	40	100	1	30	10	100	0.55	6	LV6
G425SD	40	100	1	30	10	100	0.55	6	KL4
G490SD	40	1000	3	100	30	1000	0.53	30	10F
G491SD	25	1000	3	200	20	1000	0.45	30	10T
G494SD	40	400	2	70	25	200	0.5	20	03F
G495SD	40	400	2	70	25	200	0.5	20	04F
G705SD	40	30	0.2	1	10	1	0.37	2	KL5
G706SD	45	30	0.2	1	10	1	0.37	2	LD4
GBAS40	40	200	0.6	0.2	30	40	1	5	43
GBAS40-04	40	200	0.6	0.2	30	40	1	5	44
GBAS40-05	40	200	0.6	0.2	30	40	1	5	45
GBAS40-06	40	200	0.6	0.2	30	40	1	5	46
GBAS70	70	70	0.1	0.1	50	15	1	2	B1
GBAS70A	70	70	0.1	0.1	50	15	1	2	B2
GBAS70C	70	70	0.1	0.1	50	15	1	2	B3
GBAS70S	70	70	0.1	0.1	50	15	1	2	B4
GBAT34	30	100	0.6	2	25	100	1	10	LV3
GBAT54	30	200	0.6	2	25	100	1	10	L4
GBAT54A	30	200	0.6	2	25	100	1	10	L42
GBAT54C	30	200	0.6	2	25	100	1	10	L43
GBAT54S	30	200	0.6	2	25	100	1	10	L44

量產	未量產	有樣品	工程實驗未產出
----	-----	-----	---------