

GTM ELECTRONICS

SOT-323 Schottky Diodes

Part No.	Maximum Peak Reverse Voltage	IO @T _A = 25°C	IFSM	Maximum Reverse Current @T _A = 25°C		Maximum Forward Voltage @T _A = 25°C		Cj pF	Marking Code
				I _R	V _R	I _{FM}	V _{FM}		
				uA	V	mA	V		
GS400SD	40	500	3	50	30	500	0.55	20	05F
GS401SD	30	200	3	100	30	200	0.5	40	05H
GS402SD	30	300	3	100	30	300	0.5	40	05K
GS411SD	40	500	3	30	10	10	0.3	20	05T
GS420SD	40	100	1	1	10	10	0.45	6	LV5
GS421SD	40	100	1	30	10	100	0.55	6	LV6
GS705SD	40	30	0.2	1	10	1	0.37	2	KL5
GS706SD	45	30	0.2	1	10	1	0.37	2	LD4
GS717SD	40	30	0.2	1	10	1	0.37	2	KL7
GSBAS40	40	200	0.6	0.2	30	40	1	5	43
GSBAS40-04	40	200	0.6	0.2	30	40	1	5	44
GSBAS40-05	40	200	0.6	0.2	30	40	1	5	45
GSBAS40-06	40	200	0.6	0.2	30	40	1	5	46
GSBAS70	70	70	0.1	0.1	50	15	1	2	B1
GSBAS70A	70	70	0.1	0.1	50	15	1	2	B2
GSBAS70C	70	70	0.1	0.1	50	15	1	2	B3
GSBAS70S	70	70	0.1	0.1	50	15	1	2	B4
GSBAT34	30	100	0.6	2	25	100	1	10	LV3
GSBAT54	30	200	0.6	2	25	100	1	10	L4
GSBAT54A	30	200	0.6	2	25	100	1	10	L42
GSBAT54C	30	200	0.6	2	25	100	1	10	L43
GSBAT54S	30	200	0.6	2	25	100	1	10	L44

量産	未量産	有样品	工程實驗未產出
----	-----	-----	---------