

# GTM ELECTRONICS

## SOT-323 Switching Diodes

Part No.	Repetitive Peak Reverse Voltage	IO @TA = 25°C	IFSM Surge	Maximum Reverse Current @TA = 25°C		Maximum Forward Voltage @TA = 25°C		Cj pF	Marking Code
				Ir uA	VR V	IFM mA	VFM V		
	V	mA	A						
GSBAS16	85	250	1(1mS)	1	85	150	1.25	2	A6
GSBAV70	80	200	2(1uS)	5	80	100	1.3	1.5	A4
GSBAV99W	85	150	4(1uS)	1	75	150	1.25	1.5	A7
GSBAW56	85	130	1(1mS)	1	80	150	1.25	2	A1
GSMBD2004	300	225	4(1uS)	100	240	225	1.25	5	D53
GSMBD3004	350	225	4(1uS)	100	240	100	1	5	LD6
GSMBD4148	70	200	2(1uS)	5	75	10	1	4	5H
GSN202U	80	100	4(1uS)	0.1	70	100	1.2	3.5	A3
GSN217U	80	100	4(1uS)	0.2	70	100	1.2	2	A9
GSP202U	80	100	4(1uS)	0.1	70	100	1.2	3.5	A2
GS204U	20	100	0.3(1uS)	0.1	15	10	1	2	A5
GS228U	80	100	0.3(1uS)	0.1	80	100	1.2	2	A8

量產	未量產	有樣品	工程實驗未產出
----	-----	-----	---------