

GTM ELECTRONICS

SOT-23 Shunt Regulator

Part No.	Input Voltage	Reference I/P Current MAX	Reference I/P Voltage MAX	Dynamic Impedance MAX	Off-State Cathode Current MAX	Cathode Current for Regulation MAX	Iref (Dev)	Pin Style 123
	V	uA	V	Ω	uA	mA	uA	
G431	37	4	A 2.495±0.5%	0.5	1	1	1.2	R-C-A
G431	37	4	B 2.495±1.0%	0.5	1	1	1.2	R-C-A
G431	37	4	C 2.495±2.0%	0.5	1	1	1.2	R-C-A
G431M	37	4	A 2.495±0.5%	0.5	1	1	1.2	C-R-A
G431M	37	4	B 2.495±1.0%	0.5	1	1	1.2	C-R-A
G431M	37	4	C 2.495±2.0%	0.5	1	1	1.2	C-R-A
G432	20	3.5	A 1.24±0.5%	0.5	1	0.3	1.2	R-C-A
G432	20	3.5	B 1.24±1.0%	0.5	1	0.3	1.2	R-C-A
G432	20	3.5	C 1.24±2.0%	0.5	1	0.3	1.2	R-C-A
G432M	20	3.5	A 1.24±0.5%	0.5	1	0.3	1.2	C-R-A
G432M	20	3.5	B 1.24±1.0%	0.5	1	0.3	1.2	C-R-A
G432M	20	3.5	C 1.24±2.0%	0.5	1	0.3	1.2	C-R-A

量産	未量産	有様品	工程實驗未產出
----	-----	-----	---------