

# G2310

## N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV <sub>DSS</sub>	60V
R <sub>DS(ON)</sub>	90mΩ
I <sub>D</sub>	3A

### Description

The G2310 utilized advanced processing techniques to achieve the lowest possible on-resistance, extremely efficient and cost-effectiveness device.  
The G2310 is universally used for all commercial-industrial applications.

### Features

- \*Simple Drive Requirement
- \*Small Package Outline

### Package Dimensions

SOT-23 (PACKAGE)

**N-Channel**

**Marking :**

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°

### Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V <sub>DS</sub>	60	V
Gate-Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current <sup>3</sup> , V <sub>GS</sub> @4.5V	I <sub>D</sub> @TA=25°C	3.0	A
Continuous Drain Current <sup>3</sup> , V <sub>GS</sub> @4.5V	I <sub>D</sub> @TA=70°C	2.3	A
Pulsed Drain Current <sup>1,2</sup>	I <sub>DM</sub>	10	A
Power Dissipation	P <sub>D</sub> @TA=25°C	1.38	W
Linear Derating Factor		0.01	W/°C
Operating Junction and Storage Temperature Range	T <sub>j</sub> , T <sub>stg</sub>	-55 ~ +150	°C

### Thermal Data

Parameter	Symbol	Ratings	Unit
Thermal Resistance Junction-ambient <sup>3</sup> Max.	R <sub>thj-a</sub>	90	°C/W

**Electrical Characteristics(T<sub>j</sub> = 25°C Unless otherwise specified)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	60	-	-	V	V <sub>GS</sub> =0, I <sub>D</sub> =250uA
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS} / \Delta T_j$	-	0.05	-	V/°C	Reference to 25°C, I <sub>D</sub> =1mA
Gate Threshold Voltage	V <sub>GS(th)</sub>	1.0	-	3.0	V	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA
Forward Transconductance	g <sub>fs</sub>	-	5.0	-	S	V <sub>DS</sub> =5V, I <sub>D</sub> =3A
Gate-Source Leakage Current	I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> = ±20V
Drain-Source Leakage Current(T <sub>j</sub> =25°C)	I <sub>DSS</sub>	-	-	10	uA	V <sub>DS</sub> =60V, V <sub>GS</sub> =0
Drain-Source Leakage Current(T <sub>j</sub> =70°C)		-	-	25	uA	V <sub>DS</sub> =48V, V <sub>GS</sub> =0
Static Drain-Source On-Resistance	R <sub>DS(ON)</sub>	-	-	90	mΩ	V <sub>GS</sub> =10V, I <sub>D</sub> =3A
		-	-	120		V <sub>GS</sub> =4.5V, I <sub>D</sub> =2A
Total Gate Charge <sup>2</sup>	Q <sub>g</sub>	-	6	10	nC	I <sub>D</sub> =3A V <sub>DS</sub> =48V V <sub>GS</sub> =4.5V
Gate-Source Charge	Q <sub>gs</sub>	-	1.6	-		
Gate-Drain ("Miller") Charge	Q <sub>gd</sub>	-	3	-		
Turn-on Delay Time <sup>2</sup>	T <sub>d(on)</sub>	-	6	-	ns	V <sub>DS</sub> =30V I <sub>D</sub> =1A V <sub>GS</sub> =10V R <sub>G</sub> =3.3Ω R <sub>D</sub> =30Ω
Rise Time	T <sub>r</sub>	-	5	-		
Turn-off Delay Time	T <sub>d(off)</sub>	-	16	-		
Fall Time	T <sub>f</sub>	-	3	-		
Input Capacitance	C <sub>iss</sub>	-	490	780	pF	V <sub>GS</sub> =0V V <sub>DS</sub> =25V f=1.0MHz
Output Capacitance	C <sub>oss</sub>	-	55	-		
Reverse Transfer Capacitance	C <sub>rss</sub>	-	40	-		

**Source-Drain Diode**


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage <sup>2</sup>	V <sub>SD</sub>	-	-	1.2	V	I <sub>S</sub> =1.2A, V <sub>GS</sub> =0V
Reverse Recovery Time	T <sub>rr</sub>	-	25	-	ns	I <sub>S</sub> =3A, V <sub>GS</sub> =0V di/dt=100A/μs
Reverse Recovery Charge	Q <sub>rr</sub>	-	26	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.


2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board;270°C/W when mounted on min. copper pad.


## Characteristics Curve




**Fig 1. Typical Output Characteristics**




**Fig 2. Typical Output Characteristics**




**Fig 3. On-Resistance v.s. Gate Voltage**




**Fig 4. Normalized On-Resistance v.s. Junction Temperature**




**Fig 5. Forward Characteristics of Reverse Diode**




**Fig 6. Gate Threshold Voltage v.s. Junction Temperature**




**Fig 7. Gate Charge Characteristics**




**Fig 8. Typical Capacitance Characteristics**




**Fig 9. Maximum Safe Operating Area**



**Fig 10. Effective Transient Thermal Impedance**



**Fig 11. Switching Time Waveform**



**Fig 12. Gate Charge Waveform**

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165