

G3407

P-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV _{DSS}	-30V
R _{DS(ON)}	52mΩ
I _D	-4.1A




Description

The G3407 uses advanced trench technology to provide excellent on-resistance with low gate charge. The device is suitable for use as a load switch or in PWM applications.

Features

- *Lower Gate Charge
- *Small Package Outline
- *RoHS Compliant

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V _{DS}	-30	V
Gate-Source Voltage	V _{GS}	±20	V
Continuous Drain Current ³	I _D @TA=25°C	-4.1	A
Continuous Drain Current ³	I _D @TA=70°C	-3.5	A
Pulsed Drain Current ¹	I _{DM}	-20	A
Power Dissipation	P _D @TA=25°C	1.38	W
Linear Derating Factor		0.01	W/°C
Operating Junction and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150	°C

Thermal Data

Parameter	Symbol	Ratings	Unit
Thermal Resistance Junction-ambient ³ Max.	R _{thj-a}	90	°C/W

Electrical Characteristics (T_j = 25°C unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV _{DSS}	-30	-	-	V	V _{GS} =0, I _D =-250uA
Gate Threshold Voltage	V _{GS(th)}	-1.0	-	-3.0	V	V _{DS} =V _{GS} , I _D =-250uA
Forward Transconductance	g _{fs}	-	8.2	-	S	V _{DS} =-5V, I _D =-4A
Gate-Source Leakage Current	I _{GSS}	-	-	±100	nA	V _{GS} = ±20V
Drain-Source Leakage Current(T _j =25°C)	I _{DSS}	-	-	-1	uA	V _{DS} =-30V, V _{GS} =0
Drain-Source Leakage Current(T _j =55°C)		-	-	-5	uA	V _{DS} =-24V, V _{GS} =0
Static Drain-Source On-Resistance	R _{DS(ON)}	-	-	52	mΩ	V _{GS} =-10V, I _D =-4.1A
		-	-	87		V _{GS} =-4.5V, I _D =-3.0A
Total Gate Charge ²	Q _g	-	7	-	nC	I _D =-4A V _{DS} =-15V V _{GS} =-4.5V
Gate-Source Charge	Q _{gs}	-	3.1	-		
Gate-Drain ("Miller") Change	Q _{gd}	-	3	-		
Turn-on Delay Time ²	T _{d(on)}	-	8.6	-	ns	V _{DS} =-15V V _{GS} =-10V R _G =3Ω R _L =3.6Ω
Rise Time	T _r	-	5	-		
Turn-off Delay Time	T _{d(off)}	-	28.2	-		
Fall Time	T _f	-	13.5	-		
Input Capacitance	C _{iss}	-	700	840	pF	V _{GS} =0V V _{DS} =-15V f=1.0MHz
Output Capacitance	C _{oss}	-	120	-		
Reverse Transfer Capacitance	C _{rss}	-	75	-		
Gate Resistance	R _g	-	10	-	Ω	f=1.0MHz

Source-Drain Diode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage ²	V _{SD}	-	-	-1.0	V	I _S =-1.0A, V _{GS} =0V
Reverse Recovery Time ²	T _{rr}	-	27	-	ns	I _S =-4A, V _{GS} =0V dI/dt=100A/μs
Reverse Recovery Charge	Q _{rr}	-	15	-	nC	
Continuous Source Current (Body Diode)	I _S	-	-	-2.2	A	V _D =V _G =0V, V _S =-1.0V

Notes: 1. Pulse width limited by Max. junction temperature.

2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in² copper pad of FR4 board; 270°C/W when mounted on Min. copper pad.

Characteristics Curve




Fig 1. Typical Output Characteristics




Fig 2. Transfer Characteristics




Fig 3. On-Resistance v.s. Drain Current and Gate Voltage




Fig 4. On-Resistance v.s. Junction Temperature




Fig 5. On-Resistance v.s. Gate-Source Voltage




Fig 6. Body Diode Characteristics




Fig 7. Maximum Safe Operating Area




Fig 8. Single Pulse Power Rating Junction-to-Ambient




Fig 9. Gate Charge Characteristics




Fig 10. Typical Capacitance Characteristics




Fig 11. Normalized Maximum Transient Thermal Impedance

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL: 886-3-597-7061 FAX: 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL: 86-21-5895-7671 ~ 4 FAX: 86-21-38950165