

# G2U9972

## N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BVDSS	60V
RDS(ON)	18mΩ
ID	60A

### Description

The G2U9972 provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-262 package is universally preferred for all commercial-industrial applications and suited for low voltage applications such as DC/DC converters.

### Features

- \*Simple Drive Requirement
- \*Lower Gate Charge

### Package Dimensions

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	4.40	4.80	c2	1.25	1.45
b	0.76	1.00	b2	1.17	1.47
c	0.36	0.50	L	13.25	14.25
D	8.60	9.00	e	2.54 REF.	
E	9.80	10.4	L2	1.27 REF.	

### Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	$\pm 25$	V
Continuous Drain Current, $V_{GS}@10V$	$I_D @T_C=25^\circ C$	60	A
Continuous Drain Current, $V_{GS}@10V$	$I_D @T_C=100^\circ C$	38	A
Pulsed Drain Current <sup>1</sup>	$I_{DM}$	230	A
Total Power Dissipation	$P_D @T_C=25^\circ C$	89	W
Linear Derating Factor		0.7	W/ $^\circ C$
Avalanche Current <sup>2</sup>	$I_{AR}$	30	A
Operating Junction and Storage Temperature Range	$T_j, T_{stg}$	-55 ~ +150	$^\circ C$

### Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-case Max.	Rthj-c	1.4	$^\circ C/W$
Thermal Resistance Junction-ambient Max.	Rthj-a	62	$^\circ C/W$

**Electrical Characteristics(T<sub>j</sub> = 25°C Unless otherwise specified)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	$BV_{DSS}$	60	-	-	V	$V_{GS}=0, I_D=250\mu A$
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS} / \Delta T_j$	-	0.06	-	V/°C	Reference to 25°C, $I_D=1mA$
Gate Threshold Voltage	$V_{GS(th)}$	1.0	-	3.0	V	$V_{DS}=V_{GS}, I_D=250\mu A$
Forward Transconductance	$g_{fs}$	-	55	-	S	$V_{DS}=10V, I_D=35A$
Gate-Source Leakage Current	$I_{GSS}$	-	-	±100	nA	$V_{GS}= \pm 25V$
Drain-Source Leakage Current(T <sub>j</sub> =25°C)	$I_{DSS}$	-	-	10	uA	$V_{DS}=60V, V_{GS}=0$
Drain-Source Leakage Current(T <sub>j</sub> =150°C)		-	-	25	uA	$V_{DS}=48V, V_{GS}=0$
Static Drain-Source On-Resistance <sup>3</sup>	$R_{DS(ON)}$	-	-	18	mΩ	$V_{GS}=10V, I_D=35A$
		-	-	22		$V_{GS}=4.5V, I_D=25A$
Total Gate Charge <sup>3</sup>	$Q_g$	-	32	51	nC	$I_D=35A$ $V_{DS}=48V$ $V_{GS}=4.5V$
Gate-Source Charge	$Q_{gs}$	-	8	-		
Gate-Drain ("Miller") Charge	$Q_{gd}$	-	20	-		
Turn-on Delay Time <sup>3</sup>	$T_{d(on)}$	-	11	-	ns	$V_{DS}=30V$ $I_D=35A$ $V_{GS}=10V$ $R_G=3.3\Omega$ $R_D=0.86\Omega$
Rise Time	$T_r$	-	58	-		
Turn-off Delay Time	$T_{d(off)}$	-	45	-		
Fall Time	$T_f$	-	80	-		
Input Capacitance	$C_{iss}$	-	3170	5070	pF S nA	$V_{GS}=0V$ $V_{DS}=25V$ $f=1.0MHz$
Output Capacitance	$C_{oss}$	-	280	-		
Reverse Transfer Capacitance	$C_{rss}$	-	230	-		
Gate Resistance	$R_g$	-	1.7	-		

**Source-Drain Diode**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage <sup>3</sup>	$V_{SD}$	-	-	1.2	V	$I_S=35A, V_{GS}=0V$
Reverse Recovery Time	$T_{rr}$	-	50	-	ns	$I_S=35A, V_{GS}=0V$ $di/dt=100A/\mu s$
Reverse Recovery Charge	$Q_{rr}$	-	48	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.

2. Staring  $T_j=25^\circ C$ ,  $V_{DD}=30V$ ,  $L=1mH$ ,  $R_G=25\Omega$ ,  $I_{AS}=30A$ .

3. Pulse width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .

## Characteristics Curve




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristics of Reverse Diode







Fig 6. Gate Threshold Voltage v.s. Junction Temperature




$Q_G$ , Total Gate Charge (nC)  
**Fig 7. Gate Charge Characteristics**




$V_{DS}$ , Drain-to-Source Voltage (V)  
**Fig 8. Typical Capacitance Characteristics**




$V_{DS}$ , Drain-to-Source Voltage (V)  
**Fig 9. Maximum Safe Operating Area**



$t$ , Pulse Width (s)  
**Fig 10. Effective Transient Thermal Impedance**



$V_{GS}$ , Gate-to-Source Voltage (V)  
**Fig 11. Transfer Characteristics**



**Fig 12. Gate Charge Waveform**

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165