


GMBT2714**NPN EPITAXIAL PLANAR TRANSISTOR****Description**


The GMBT2714 is designed for use in FM, RF, MIX and IF amplifier application.

Features

- High frequency
- Very low capacitance

Package Dimensions

Marking :



□ : hFE Rank Code

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°

Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Ratings	Unit
Junction Temperature	Tj	+150	°C
Storage Temperature	Tstg	-55~+150	°C
Collector to Base Voltage	VCBO	40	V
Collector to Emitter Voltage	VCEO	30	V
Emitter to Base Voltage	VEBO	4	V
Collector Current	IC	20	mA
Total Power Dissipation	PD	225	mW






Electrical Characteristics (Ta = 25°C, unless otherwise noted)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	40	-	-	V	IC=100uA, IE=0
BVCEO	30	-	-	V	IC=1mA, IB=0
BVEBO	4	-	-	V	IE=10uA, IC=0
ICBO	-	-	500	nA	VCB=18V, IE=0
IEBO	-	-	500	nA	VEB=4V, IC=0
VCE(sat)	-	-	500	mV	IC=4mA, IB=0.4mA
VBE(on)	-	-	950	mV	VCE=10V, IC=4mA
hFE	40	-	200		VCE=6V, IC=1mA
fT	650	-	-	MHz	VCE=10V, IC=4mA, f=100MHz
Cob	-	0.8	-	pF	VCB=10V, f=1MHz

Classification Of hFE

Rank	R	O	Y
Range	40 ~ 80	70 ~ 140	100 ~ 200

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165