



WTD0001

Touch Screen Controller (For SPI Interface)

WTD0001

Touch Screen Controller

(SPI Interface)

REV. 1. 01

May, 18, 2001

E-Tech Electronics Ltd.

Hong Kong Headquarters:

Unit D, 3/F., Unison Industrial Centre,
27-31 Au Pui Wan Street, Fo Tan, Shatin, N.T. H.K.
Tel.: (852) 2607 0218 Fax (852) 2607 0155
E-Mail: mktg@e-tech.com.hk
Web Site: <http://www.e-tech.com.hk>

ShenZhen Branch:

Unit 1403, 14/F, Pacific Commercial Building,
Chia Pin Road, ShenZhen, China
Tel: (0755) 2136 018 Fax: (0755) 2136 008
E-Mail: sales_sz@e-tech.com.hk



General Description

WTD0001 serial controllers are designed for electronic product which using four-wired resistance touch screen, for example PDA and LCD Module. The purpose is to lower Host control affording in resistance touch screen to make your product can connect touch screen easily, and add your product additional value.

In hardware, the extra element is cheap materials, for example resistance, diode and capacitance; it needs not expensive quartz; package in SSOP 20 pin can lower your acreage in PCB.

WTD0001 includes function for software filter; it can filter out unnecessary noise to lower flying-line producing rate.

In addition, WTD0001 provides 3-channel, 12-bit A/D converter it can be adapted in many application for example battery voltage detector and charger.

Features

- 8-bit micro controller base
- 12-bit resolution analog to digital converter
- Direct driving Touch Screen no external transistors are required
- Touch pressure could be measure
- Debounce and noise filter function
- Automatic wake up from screen touch (also could be disable)
- Automatic standby power down function
- 3-channel, 12-bit A/D converter
- 4 wire serial interface
- Standby current less then 1 μ A @3V
- Single Supply 2.4V to 5V
- 20 Pin SSOP package



WTD0001

Touch Screen Controller (For SPI Interface)

Pin Assignment

Yh	1	20	VDD
Xl	2	19	AIN3
Yl	3	18	AIN2
Xh	4	17	AIN1
VDD	5	16	WakeUp
DI	6	15	DO
INT	7	14	WR
RIN	8	13	SK
CLK	9	12	VDD
GND	10	11	RESET

WTD0001

20 pin SSOP

Pin Description

PIN#	NAME	DESCRIPTION
1	Yh	Connect to Y panel bottom side
2	Xl	Connect to X panel left side
3	Yl	Connect to Y panel top side
4	Xh	Connect to X panel right side
5	VDD	Connect to power source
6	DI	Serial port data input
7	INT	Ready to communication
8	RIN	Connect to power source
9	CLK	Internal ring oscillator output
10	GND	Connect to power ground
11	RESET	Device reset input low active
12	VDD	Connect to power source



WTD0001

Touch Screen Controller (For SPI Interface)

13	SK	Serial port clock input
14	WR	Write signal
15	DO	Serial port data output
16	WakeUp	Detect pen down signal or Write signal via diode
17	AIN1	A/D converter channel 1 input pin
18	AIN2	A/D converter channel 2 input pin
19	AIN3	A/D converter channel 3 input pin
20	VDD	Connect to power source